



SAFETY DATA SHEET

SECTION 1 — PRODUCT IDENTIFICATION

Product identifier: Albatross® Difficult Stains Premium

Product Number: 1013R, 1116R, 1118R

Product use: Spot cleaning of apparel and textiles.

Manufacturer's name and address: Refer to supplier

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300
(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with 29CFR 19190.1200 (Hazard Communication Standard) and WHMIS regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

SECTION 2 — HAZARDOUS IDENTIFICATION

DANGER!



HAZARD STATEMENTS:

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment
P280	Wear protective gloves and eye / face protection.

RESPONSE:

- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312: Call a POISON CENTER/doctor if you feel unwell.
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P330: Rinse mouth.
 P303+P361+P353: IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing.
 Rinse skin with water/shower.
 P331: Do NOT induce vomiting.
 P332+P313: If skin irritation occurs: Get medical advice/attention.
 P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

STORAGE/DISPOSAL

- P391 Collect spillage.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents and container in accordance with local regulation.

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

<u>MATERIAL</u>	<u>CAS #</u>	<u>EINECS #</u>	<u>WT %</u>
Synthetic Isoparaffinic Hydrocarbon	64741-66-8	-	40-50
Synthetic Isoparaffinic Hydrocarbon	64742-48-9	-	20-30
1,2-trans-Dichloroethylene	156-60-5	-	30-40
1,1,2,2-Tetrafluoroethyl-2,2,2-Trifluoroethyl ether	406-78-0	-	3-10

SECTION 4 — FIRST AID MEASURES

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapour exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SWALLOWING:

Rinse mouth.. Do NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

SECTION 5 — FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES:

No open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof equipment, lighting.

EXTINGUISHING MEDIA:

Use dry powder, carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES:

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES:

Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Closed containers may explode if exposed to extreme heat.
Applying to hot surfaces requires special precautions.
Empty container very hazardous! Continue all label precautions!

SECTION 6 — ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE MEASURES:

Vapors may ignite explosively & spread long distances. Prevent vapour buildup.
Keep unprotected personnel away.
Ventilate spill area. Remove all ignition sources.
Filter respirator for organic vapors.

ENVIRONMENTAL PRECAUTIONS:

Keep from entering storm sewers and ditches which lead to waterways.

CONTAINMENT AND CLEAN-UP MEASURES:

Stop spill at source. Dike and contain.
Absorb remaining liquid in sand or inert absorbent.

SECTION 7 — HANDLING AND STORAGE

HANDLING:

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation.
Avoid breathing of vapour or spray mist. Do not get in eyes, on skin or clothing.
Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.
Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld.
Empty container very hazardous! Continue all label precautions!
Drinking alcohol shortly before, during or after use can cause unwanted effects.
To minimize static discharge when transferring, ensure electrical continuity by bonding and grounding all Equipment. Use an inlet line diameter of at least 3.5 inches (8.9 centimeters) with a maximum flow rate of 1 meter/second.

STORAGE:

Isolate from strong oxidants. Do not store above 49 C/ 120 F.

Contact with hot surfaces can produce toxic gases.
 Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>MATERIAL</u>	<u>CAS #</u>	<u>EINECS #</u>	<u>TWA(OSHA)</u>	<u>TLV(EXXON)</u>
Synthetic Isoparaffinic Hydrocarbon	64741-66-8	-	None Known	281 ppm
Synthetic Isoparaffinic Hydrocarbon	64742-48-9	-	None Known	191 ppm

<u>MATERIAL</u>	<u>CAS #</u>	<u>EINECS #</u>	<u>TWA(OSHA)</u>	<u>TLV(ACGIH)</u>
Trans-1,2-Dichloroethylene	156-60-5	-	N/A	200 ppm

<u>MATERIAL</u>	<u>CAS #</u>	<u>EINECS #</u>	<u>EPA 8hr TWA</u>	<u>EPA-CEILING</u>
1,1,2,2-Tetrafluoroethyl-2,2,2-trifluoroethyl ethyl	406-78-0	-	75ppm	150 ppm

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

RESPIRATORY EXPOSURE CONTROLS:

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator’s use.

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

WORK & HYGIENIC PRACTICES:

- Provide readily accessible eye wash stations & safety showers.
- Wash at end of each workshift & before eating, smoking or using the toilet.
- Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles.
- Launder or discard contaminated clothing.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid, Water-White
Odor	Ester
Odor threshold	Not Available
pH (Neutrality):	Not applicable
Melting point/Freezing point:	Not Available
Boiling range	48°C - 179°C
Flash point (Test Method)	> 200°F (TCC)
Evaporation Rate (n-Butyl acetate+1)	Not applicable
Lower flammable limit in air	Not Available
Upper flammable limit in air	Not Available
Vapour pressure (mm of hg) @20 C	Not Available
Vapour density (Air=1)	Not Available
Gravity @ 68/68 F/ 20/20 C	
Specific gravity (water=1)	0.907
Pounds/gallon	7.255

Water solubility	Negligible
Partition coefficient (n-Octane/water)	Not Available
Auto ignition temperature	Not Available
Decomposition temperature	Not Available
Voc's (>0.44 Lbs/Sq In)	0.00 vol % / 0.00 g/l / 0.000 lbs/gal
Total Voc's (TVOC)*	100.0 Vol% / 860.0 g/l / 7.255 lbs/gal
Nonezempt Voc's (CVOC)*	97.0 Vol% / 827.0 g/l / 6.89 lbs/gal
Hazardous air pollutants (HAPS)	0.0 wt% / 0.0 g/l / 0.00 lbs/gal
Non-exempt voc partial pressure (mm of hg @ 20 C)	N.E.

*Using California South Coast Air Quality Management District (SCAQMD) rule 443.1

SECTION 10 — REACTIVITY AND STABILITY DATA

Stability:

Stable under normal conditions.

Conditions to avoid:

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

Materials to avoid:

Reacts with strong oxidants, causing fire & explosion hazard.

Hazardous decomposition products:

Carbon monoxide, carbon dioxide, hydrogen chloride, phosgene, hydrogen bromide, bromine from burning.

Hazardous polymerization:

Will not occur.

SECTION 11 — TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

Synthetic Isoparaffinic Hydrocarbon (64741-66-8)

Inhalation (rat): 4 hours LC50 >21 mg/l (vapor)

Ingestion (rat): LD50 > 5000 mg/kg

Dermal (rabbit): LD50 >2000 mg/kg

Synthetic Isoparaffinic Hydrocarbon (64742-48-9)

Inhalation (rat) 8 hours LC50 > 5000 mg/m3 (vapor)

Ingestion (rat): LD50 >5000 mg/kg

Trans-1,2 Dichloroethylene

Oral LD50 (rat): 1.392 mm/kg

Dermal LD50(rabbit): 5,000 mg/kg

1,1,2,2-Tetrafluoroethyl-2,2,2-trifluoroethyl ether

Oral LD50 (rat): >2,000 mg/kg

Dermal LD50(rat): >2,000 mg/kg

Particles/mist LC50, inhalation LD 50 (rat): >24.8 mg/L (3,010 ppm)

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.

Primary irritation to eyes, redness, tearing, blurred vision.

Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression which can cause death. Vapor harmful.
Concentrated vapour in confined areas may be fatal.

SWALLOWING:

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.
The symptoms of chemical pneumonitis may not show up for a few days.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED**CONDITIONS AGGRAVATED:**

Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS**CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.

SECTION 12 — ECOLOGICAL INFORMATION**AQUATIC ANIMAL INFORMATION:**

No aquatic environmental information is available on this product.

MOBILITY IN SOIL:

This material is a mobile liquid.

DEGRADABILITY:

This product is partially biodegradable.

ACCUMULATION:

Bioaccumulation of this product has not been determined.

SECTION 13 — DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste management options. Recycle/dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If in doubt, contact appropriate agencies.

SECTION 14 — TRANSPORTATION INFORMATION

DOT SHIPPING NAME:	Not Regulated
DRUM/LABEL:	Not Regulated
IATA/ICAO:	Not Regulated.
IMO/IMDG:	Not Regulated

EMERGENCY RESPONSE GUIDEBOOK NUMBER: None

SECTION 15 — REGULATORY INFORMATION

EPA REGULATION:

SARA Section 311/312 HAZARDS: Acute Health

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated (*) toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS #	EINECS #	WT% (REG.SECTION)	RQ(LBS)
None				

CALIFORNIA PROPOSITION 65:

None

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

D2B: Irritating to skin/eyes

SECTION 16 — OTHER INFORMATION

HMIS HAZARD RATINGS:

HEALTH: * 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 PERSONAL PROTECTION: X

HAZARD RATING KEY:

4 = Extreme, 3 = High, 2 = Moderate, 1 = Slight, 0 = Insignificant, * = Chronic Health Hazard.
 X = Ask Supervisor - Personal Protection Rating to be supplied by user based on use conditions.
 This information is intended solely for the use of individuals trained in the HMIS hazard Rating systems.

EMPLOYEE TRAINING:

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this Material (as stated in this SDS) before handling it.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore, users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 03/23/2020.

Prepared by: Albatross USA Inc.
Telephone number: 718-392-6272
Preparation Date: March 23, 2017
Revision Date: October 30, 2017