



# SAFETY DATA SHEET

## SECTION 1 — IDENTIFICATION

**Product identifier:** AlbaChem® Dri-Web Foam Adhesive Spray  
**Product Number:** 1075  
**Recommended Use:** Adhesive  
**Recommended restrictions:** None known

### ***ALBATROSS USA INC./EXPERT WORLDWIDE***

36-41 36<sup>th</sup> Street  
 Long Island City, New York  
 United States  
 11106  
 718-392-6272

5439 San Fernando Road West  
 Los Angeles, California  
 United States  
 90039  
 818-543-5850

**Emergency Telephone #:** Chemtrec (Day or Night) 800-424-9300  
 (For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)  
 This MSDS complies with 29CFR 19190.1200 (Hazard Communication Standard) and WHMIS regulations.

**IMPORTANT:** Read this MSDS before handling and disposing of this product. Pass this information on to employees, customer, and users of this product.

## SECTION 2 — HAZARD(S) IDENTIFICATION

<b>Physical hazards</b>	Flammable aerosols	Category 1
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified	
<b>OSHA defined hazards</b>	Not classified	



**Label elements**

**Signal word**

Danger

**Hazard statement**

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement**

**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not breathe gas.

<b>Response</b>	Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Not available
<b>Hazard(s) not otherwise Classified (HNOC)</b>	None known
<b>Supplemental information</b>	None

### SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20-40
Propane		74-98-6	20-40
Dimethyl Ether		115-10-6	10-20
n-Hexane		110-54-3	10-20
2-Methylpentane		107-83-5	2.5-10
3-Methylpentane		96-14-0	1-2.5
Other components below reportable levels			10-20

\*Designates that a specific chemical identity and/or percentage or composition has been withheld as a trade secret.

### SECTION 4 — FIRST AID MEASURES

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned. Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### SECTION 5 — FIRE FIGHTING MEASURES

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Dry powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing</b>	Do not use water jet as an extinguisher, as this will spread the fire.

**media**

**Specific hazards arising from the chemical** Contents under pressure. Pressurized container may explode when exposed to heat or flame.

**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire-fighting equipment/instructions** Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

**General fire hazards** Extremely flammable aerosol.

## SECTION 6 — ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protections, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## SECTION 7 — HANDLING AND STORAGE

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hand thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

## SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational exposure limits

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	STEL	2 ppm
	TWA	0.75 ppm

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup> 1000 ppm
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m <sup>3</sup> 500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m <sup>3</sup> 1000 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm
	TWA	500 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Dimethyl Ether (CAS 115-10-6)	Ceiling	0.3 ppm
	TWA	50 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup> 250 ppm
	Ceiling	0.1 ppm
Dimethyl Ether (CAS 115-10-6)	TWA	0.016 ppm
	TWA	180 mg/m <sup>3</sup> 50 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup> 1000 ppm

#### US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m <sup>3</sup>
		1000 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-hexanedion without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US – California OELs: Skin designation**

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection** Wear safety glasses with side shields (or goggles).**Hand protection**

Wear appropriate chemical resistant gloves.

**Skin protection****Other skin protection**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection**

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES****Appearance****Physical state**

Gas

**Form**

Aerosol

**Color**

Not available

**Odor**

Not available

**Odor Threshold**

Not available

**pH**

Not available

**Melting point/freezing point**

Not available

**Initial boiling point and boiling range**

122.33°F (50.18°C) estimated

**Flash point**

-156.0°F (-104.4°C) PROPELLANT estimated

**Evaporation rate**

Not available

**Flammability (solid, gas)**

Not available

**Upper/lower flammability or explosive limits****Flammability limit – lower (%)**

2.2% estimated

**Flammability limit – upper (%)**

8.6% estimated

**Explosive limit – lower (%)**

Not available

**Explosive limit – upper (%)**

Not available

**Vapor pressure**

62 psig @70F estimated

**Vapor density**

Not available

**Relative density**

Not available

**Solubility(ies)****Solubility (water)**

Not available

**Partition coefficient (n-octanol/water)**

Not available

**Auto-ignition temperature**

599.06°F (315.03°C) estimated

<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	Not available
<b>Other information</b>	
<b>Specific gravity</b>	0.724 estimated

## SECTION 10 — STABILITY AND REACTIVITY

<b>Reactivity</b>	This product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known

## SECTION 11 — TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation
<b>Eye contact</b>	Causes serious eye irritation
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways. Narcotic effects.
-----------------------	---

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 hours > 9.4 ml/kg, 24 hours
	Rabbit	> 7426 mg/kg, 24 hours > 9.4 ml/kg, 24 hours 20 mg/kg
<i>Inhalation.</i>		
LC50	Rat	55700 ppm, 3 hours 132 mg/l, 3 hours 50.1 mg/l
<i>Oral</i>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg 2.2 ml/kg
<i>Other</i>		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg

## Dimethyl Ether (CAS 115-10-6)

**Acute***Inhalation*

NOEL Rat 2 ppm, 6 Hours

*Oral*

LD50 Rat 460 mg/kg

## n-Hexane (CAS 110-54-3)

**Acute***Dermal*LD50 Rabbit >2000 mg/kg, 4 Hours  
>5 ml/kg, 4 Hours*Inhalation*LC50 Rat >5000 ppm, 24 Hours  
>31.86 mg/l  
73860 ppm, 4 Hours*Oral*LD50 Rat 24 ml/kg  
24 g/kg  
Wistar rat 49 g/kg

## Propane (CAS 74-98-6)

**Acute***Inhalation*LC50 Mouse 1237 mg/l, 120 Minutes  
52%, 120 Minutes  
Rat 1355 mg/l  
658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation**Serious eye damage/eye irritation** Causes serious eye irritation**Respiratory or skin sensitization****Respiratory sensitization** Not available**Skin sensitization** This product is not expected to cause skin sensitization**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed

**Reproductive toxicity** Suspected of damaging fertility**Specific target organ toxicity - single exposure** - May cause drowsiness and dizziness**Specific target organ toxicity - repeated exposure** - Respiratory system. Skin. Eyes. Nervous system. Peripheral nervous system. May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard** May be fatal if swallowed and enters airways**Chronic effects** Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.**SECTION 12 — ECOLOGICAL INFORMATION****Ecotoxicity** Toxic to aquatic life with long lasting effects

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
12 OZ. ALBATROSS DRI-WEB FOAM (CAS Mixture)		
<b>Aquatic</b>		
Crustacea	EC50 Daphnia	91,7423 mg/l, 48 hours estimated
Fish	LC50 Fish	1728322 mg/l 96 hours estimated

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 21.6-23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 -06330 mg/l, 96 hours
Dimethyl Ether (CAS 115-10-6)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia pulex</i> ) 4.3 – 7.8 mg/l, 48 hours
Fish	LC50	Striped bass ( <i>Morone saxatilis</i> ) 10.302 – 16.743 mg/l, 96 hours
n-Hexane (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 2.101 – 2.981 mg/l, 96 hours

\*Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product

**Bioaccumulative potential** No data available

**Partition coefficient n-octanol/water (log Kow)**

2-Methylpentane	3.74
3-Methylpentane	3.6
Acetone	-0.24
Dimethyl Ether	0.1
n-Hexane	3.9
Propane	2.36

**Mobility in soil** No data available

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13 — DISPOSAL CONSIDERATIONS

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>US RCRA Hazardous Waste U List: Reference</b>	
Acetone (CAS 67-64-1)	U002
<b>Waste from residue/unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

## SECTION 14 — TRANSPORT INFORMATION

**DOT**

**UN number** UN1950



<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
<b>Packing group</b>	Not applicable
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirement of section 173.306 as a limited quantity and may be shipped as a limited quantity Until 12/31/2020, the “Consumer Commodity – ORM-D” marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the “Consumer Commodity ORM-D” marking and both may be displayed concurrently.

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
<b>Packing group</b>	Not applicable
<b>Environmental hazards</b>	Yes
<b>ERG code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed
<b>Cargo aircraft only</b>	Allowed
<b>Packaging exceptions</b>	LTD QTY

**IMDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
<b>Packing group</b>	Not applicable
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Packaging exceptions</b>	LTD QTY
<b>Transport in bulk</b>	Not applicable

According to Annex  
II of MARPOL 73/78  
And the IBC Code

## DOT



## IATA; IMDG



## Marine Pollutant



## General information

IMDG Regulated Marine Pollutant

### SECTION 15 — REGULATORY INFORMATION

## US Federal Regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

## CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed

n-Hexane (CAS 110-54-3)

Listed

## SARA 304 Emergency release notification

Not regulated

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## Hazard categories

Immediate Hazard – Yes

Delayed Hazard – Yes

Fire Hazard – Yes

Pressure Hazard – Yes

Reactivity Hazard – No

## SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Phenol	108-95-2	1000		500 lbs	10000 lbs

SARA 311/312 Hazardous chemical

## SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
n-Hexane	110-54-3	10 – 20
Ethyl Benzene	100-41-4	0.01 – 0.1

Styrene 100-42-5 0.01 – 0.1

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

n-Hexane (CAS 110-54-3)

**Clean Air Act (CAA Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Dimethyl Ether (CAS 115-10-6)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1) 6532

**Drug Enforcement Administration (DEA) List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Acetone (CAS 67-64-1) 35% WV

**DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1) 6532

**US state regulations****US. Massachusetts RTK – Substance List**

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

**US. New Jersey Worker and Community Right-to-Know Act**

2-Methylpentane (CAS 107-83-5)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

**US. Rhode Island RTK**

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**International Inventories**

Country(s) or region	Inventory name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A “Yes” indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A “No” indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

<b>SECTION 16 — OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION</b>
---

<b>Issue date</b>	04-03-2015
<b>Version #</b>	01
<b>Prepared by</b>	Albatross USA Inc.
<b>Telephone number</b>	718-392-6272

**.Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless pecified in the text.

**Revision information** GHS: Classification